81-QSVM "Quick Stand" Installation Instructions




ONLY WHEN TANK IS EMPTY, remove sprayer from truck as follows:


- 1. Install rear jack stands into boom center section pipe, one on each side of boom. Extend jack until weight is lifted off rear pivot pins. **DO NOT REMOVE PINS YET!**
- 2. Tilt sprayer.
- 3. Install mounting flange to sprayer frame using holes provided in frame.
- 4. Install front legs on mounting flange and install bolts (provided).
- 5. Lower sprayer so legs are supporting front of sprayer and cylinder pins are free in their holes. **DO NOT REMOVE PINS YET!**
- 6. Remove rear pivot pins and jack up rear of sprayer approximately 1 to 2 inches.
- 7. Unplug hydraulic hoses from truck.
- 8. Disconnect control cable from console and coil up on back of boom.
- 9. Drive truck out from under sprayer.

To Install Sprayer on Truck:

- 1. Back truck under sprayer until rear pivot pinholes are close to rear pivot pinholes on truck.
- 2. Lower jacks until pin holes line up and pins can be installed.
- 3. Crank jacks so they are off the floor an inch or so.
- 4. **RAISE** sprayer enough to raise front stands off floor. Remove bolt and slide stands off frame. Leave flange mount attached to sprayer frame for future use.
- 5. Lower sprayer and install front hold down clamps, reroute wire harness and plug into console.
- 6. Remove rear jacks and brackets from boom tube.
- 7. Plug in hydraulic lines and controls.





When installing on "Windbreaker 2000" Boom.



Side view of 81-QSVM.







Insert B

