



Item No.	Part No.	Description	Qty
1	69-284	Eye Bolt 3/8 x 5"	2
2	69-242	S-Hook 2"	4
3	69-930	Chain 1/0 Per Foot	2 Pieces 5' Each
4	11-057	Anchor Bracket	2

1. Install skid sprayer into utility vehicle box with boom side out to rear. Boom should be installed to assure clearance of boom center spray bar clearance before fastening skid sprayer into box.
2. Short box will show some rear over-hang on some trucks. If over-hang is more than 20% of total sprayer length, consult factory for alternate mounting methods.
3. Long box may require the use of a 4 x 4 spacer block or equivalent. Spacers should fit snug and cross the complete width of the utility box.
4. Install anchor bracket to spray tank flange on flat or angled slope. If tank has angled slope, this works best. Position anchors equally on each side of the tank flange. Use 3/8" hardware supplied. Use flat washer on bare fiberglass (side opposite anchor bracket).
5. Hook one end of chain with S-Hooks, into ring on eyebolt (crimp S closed). Stretch chain and hook other end of S-Hook into hole in lower corner of utility box. If no hole is available, drill one on lower or bottom of side wall on box. Install S-Hook into new hole.
6. Using box wrench, draw (tighten) eyebolt ring towards the back of the anchor bracket until slack is gone from the chain. This will secure the box down and into the front of the utility box. **Do not raise** dump box while sprayer is mounted.
7. If sprayer is a permanent mount, we suggest that bolts through sprayer sub-frame be attached directly to the utility bed floor.