



Optimum Turf Boom



SDI has designed the Optimum Turf Boom to use the best features of wet and dry style booms.

- Easily mounts to any SDI manufactured sprayer.
- Our precision welded nozzle mounts provide accurate nozzle positioning.
- Bi-directional breakaway hinges that fold upward or forward for storage.
- Triple outlet nozzle bodies allow you quick changes of nozzle patterns or flow rates without the need for additional tools.

| Model | Width | Spacing | Nozzles |
|----------------|--------------------------|-----------|---------|
| OTB215/20-3 | 15 feet | 20 inches | 9 |
| OTB215/10-3 | 15 feet | 10 inches | 17 |
| OTB218/20-3 | 18 feet | 20 inches | 11 |
| OTB215-21/20-3 | 15 - 21 feet convertible | 20 inches | 13 |

Features of the SDI Optimum Turf Booms:

- 15, 18 or 15/21 foot widths.
- 10 or 20 inch nozzle spacing available on the 15 foot booms.
- Triple outlet SDI nozzle bodies for quick rate changes.
- Welded steel, epoxy coated construction with precision welded nozzle mounts.
- Standard gauge wheels protect nozzle bodies and boom wing ground strikes.
- Bi-directional breakaway hinges provide wing protection when travelling forward or backward.



Triple Nozzle Body



Forward Folding Boom

- **New** forward folding feature provides clearance from obstacles or storage buildings with low ceilings.

- **OPTIONS:** Hydraulic/Electric boom lift actuators for “on the go” boom adjustment. The ground contour wheel kit maintains a consistent boom height when travelling over undulating terrain.



Hydraulic/Electric Actuator



Ground Contour Wheel



Standard Gauge Wheel

Spraying Devices Inc. • 447 E. Caldwell Ave • Visalia, CA 93277
(559)734-5555 • www.sprayingdevices.com
sales@sprayingdevices.com